

Hayes Accura ISDN PCI Terminal Adaptor

PCI ISDN Terminal Adaptor works with Basic Rate S/T Interface

Channel Bonding for speeds up to 128 Kbps

Plug and Play for easy installation

14,400 bps fax

CAPI 2.0 compatible (works with popular ISDN software)

Flash memory for easy firmware updates

Voice mail supported (requires sound card)

ISDN Terminal Adaptor for Windows® 95, 98, 2000, ME & NT4.0

The Hayes Accura ISDN PCI Terminal Adaptor connects to the world's most popular ISDN interface, the 'Basic Rate S/T Interface' which provides two 64 Kbps B channels and one D signalling channel.



By using the ML-PPP standard, the two B channels can be bonded together to give 128 Kbps throughput uncompressed, more than double the speed of a 56K modem.

Because the ISDN line provides two B channels, multitasking is possible, for example, a fax can be sent on one channel while the computer user can browse the Web on the other channel.

Call Bumping and Bandwidth on Demand features are also supported.

The Terminal Adaptor supports both the CAPI 2.0 and NDIS WAN miniport drivers to provide a high level of application software compatibility. All the popular ISDN protocols are supported, including Eurofile transfer.

Technical Specifications

Data Speeds

- Channel bonding for speeds up to 128 Kbps

Fax Speeds

- 14,400 Kbps, Group 3, Class 1

Standards Supported

- Point-to-Point Multilink Protocol (MLP) with 128 Kbps Channel Bonding
- V.110 and V.120 Rate Adaptation
- Async to Sync PPP Conversion
- V.42 bis Data compression over ISDN

Standards Supported (cont.)

- HDLC transparent, X.75, T.70NL, Eurofile transfer on B channels
- Automatic Protocol Sensing (V.110, V.120, X.75, PPP, MLP)

Operating System Support

- Windows 95, 98, ME, NT4.0 and 2000

Regulatory Approvals

- CE Approved

Hayes Accura ISDN PCI Terminal Adaptor

Product Package Contains

- Hayes Accura PCI ISDN Terminal Adaptor
- 2 Metre RJ-45 ISDN Telephone cable
- CD-Rom with Software and Drivers
- User's Guide

Warranty

- One year

System Requirements

- Standard ISDN Basic Rate phonenumber with S/T Interface
- 486, Pentium or faster PC
- Windows 95, 98, 2000 ME or NT4.0
- Hard drive with 2MB disk space
- Available PCI slot



430 Frimley Business Park,
Frimley,
Camberley,
Surrey, GU16 7SY

Tel: +44 (0)1276 704400
Fax: +44 (0)1276 704500
URL: <http://www.hayes.co.uk>